IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of

Atty. Ref.: 511-57

BROSSEUK

Serial No. 10/814,786

Group:

Not Yet Assigned

Filed: April 1, 2004

Examiner: Not Yet Assigned.

For: STEERING MECHANISM FOR WATERCRAFT

June 4, 2004

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Sir:

SUBMISSION OF PRIORITY DOCUMENT

It is respectfully requested that this application be given the benefit of the foreign filing date under the provisions of 35 U.S.C. §119 of the following, a certified copy of which is submitted herewith:

Application No.

Country of Origin

Filed

2003/2710

South Africa

4 April 2003

It is respectfully requested that the Examiner acknowledge the above-noted claim for priority and receipt of the priority document.

While it is believed that no fee is due at this time, the Commissioner is hereby authorized to charge any <u>deficiency</u> in the fee(s) filed, or asserted to be filed, or which should have been filed herewith (or with any paper hereafter filed in this application by this firm) to our **Account No. 14-1140.**

Respectfully submitted,

NIXON & VANDERHYE P.C.

By: Pobert A. Molan

Robert A. Molan Reg. No. 29,834

RAM:drt 1100 North Glebe Road, 8th Floor Arlington, VA 22201-4714

Telephone: (703) 816-4000 Facsimile: (703) 816-4100

Sertifikaat

TABLE LIFE

Certificate

REPULIEK VAN SUID AFRIKA

REPUBLIC OF SOUTH AFRICA

PATENT KANTOOR DEPARTEMENT VAN HANDEL EN NYWERHEID PATENT OFFICE DEPARTMENT OF TRADE AND INDUSTRY

Hiermee word gesertifiseer dat This is to certify that

- South African Provisional Patent Application No. 2003/2710 accompanied by a Provisional Specification was filed at the South African Patent Office on 4 April 2003, in the name of BROSSEUK, Raymond Brian in respect of an invention entitled: "Steering mechanism for watercrafts."
- 2) On 20 February 2004 an assignment of South African Patent Application No. 2003/2710 from BROSSEUK, Raymond Brian to IE-TEC Licensing Limited was recorded at the South African Patent Office.
- 3) The photocopy attached hereto is a true copy of the provisional specification and drawings filed with South African Patent Application No.2003/2710.

Geteken te

DDETODIA

in die Republiek van Suid-Afrika, hierdie

dag van

21th

Signed at

in the Republic of South Africa, this

April 2004

day of

uay oi

Registrar of Patents

												Form
REPUBLIC OF SOUTH AFRICA		RE	GISTER C	F PA	ENTS					PATE	NTS A	CT, 197
OFFICIAL APPLICATION NO.	1	LODGING	DATE : PR	OVISIO	NAL		ACC	EPTA	NCE D	ATE		
21 014 200 8 / 27 4	n	22 4 Ap	ril 2003				43					
INTERNATIONAL CLASSIFICATION	V		DATE : CO	OMPLE	TE		GRA	NTED	DATE	:	_	
51		23	·				T					
FULL NAME(S) OF APPLICANT(S) /	PATEN	TEE(S)										
71 BROSSEUK, Raymond Brian							•					
										•		
					*							
•												
											•	
· · · · · · · · · · · · · · · · · · ·							•					
APPLICANTS SUBSTITUTED :										GISTER		
71 LE-CEE Li	ي جي	~3 0 C M	ia A	DENIA	TREES	8/AIRTH	YMAY!		20	· 60 >	- 0.0	P.
<u> </u>			AP	PLICA	NTS S	SUBST	11101	4				
		.						ļ				
ASSIGNEE(S)								DA	TE RE	GISTER	ED	
71			-				· .					
								ļ.,				
FULL NAME(S) OF INVENTOR(S)												
72 BROSSEUK, Raymond Brian											·	
72 BROSSEUK, Raymond Brian			•							3		
72 BROSSEUK, Raymond Brian							-			;		
BROSSEOR, Raymond Bhan	UNTRY			NUMI	BER				DATE	;		
PRIORITY CLAIMED CO	UNTRY	(NUMI	BER				DATE)		
PRIORITY CLAIMED CO N.B. Use international abbreviation for country.	UNTRY			NUMI	BER				DATE	;		
PRIORITY CLAIMED CO	UNTRY				BER		-					
PRIORITY CLAIMED CO N.B. Use international abbreviation for country.	UNTRY				BER					;		
PRIORITY CLAIMED CO N.B. Use international abbreviation for country.	UNTRY	,			BER					•		
PRIORITY CLAIMED CO N.B. Use international abbreviation for country. (See Schedule 4) TITLE OF INVENTION					BER					;		
PRIORITY CLAIMED N.B. Use international abbreviation for country. (See Schedule 4) TITLE OF INVENTION					BER					;		
PRIORITY CLAIMED CO N.B. Use international abbreviation for country. (See Schedule 4) TITLE OF INVENTION					3ER					; <u> </u>		
PRIORITY CLAIMED N.B. Use international abbreviation for country. (See Schedule 4) TITLE OF INVENTION 54 STEERING MECHANISM FOR WA	FERCRA	AFT			BER					:		
PRIORITY CLAIMED CO N.B. Use international abbreviation for country. (See Schedule 4) TITLE OF INVENTION	FERCRA	AFT S)	AR FOR	31			3,		32		Man	STOR
PRIORITY CLAIMED N.B. Use international abbreviation for country. (See Schedule 4) TITLE OF INVENTION 54 STEERING MECHANISM FOR WATER STEERING FOR WATER STEERIN	FERCRA	AFT S)	Ne Fora	31		\$			32		Ass.	STRE
PRIORITY CLAIMED N.B. Use international abbreviation for country. (See Schedule 4) TITLE OF INVENTION 54 STEERING MECHANISM FOR WATER STEERING FOR WATER STEERING FOR WATER STEERING FOR WA	NTEE(S	AFT S) Source of the second of		31		\$ C	REF	:	32	90	Ass.	STRA
PRIORITY CLAIMED N.B. Use international abbreviation for country. (See Schedule 4) TITLE OF INVENTION 54 STEERING MECHANISM FOR WATA ADDRESS OF APPLICANT(S) / PATE 1810 Marley Road Revelstoke British Columbia Canada V03 2S0 Canada ADDRESS FOR SERVICE 74 D M Kisch Inc, 54 Wierda Road W	NTEE(S	AFT S) Seeks	SANDTON	31		>&		:	32		~~~	STRA
PRIORITY CLAIMED N.B. Use international abbreviation for country. (See Schedule 4) TITLE OF INVENTION 54 STEERING MECHANISM FOR WATER STEERING FOR WATER STEERING FOR WATER STEERING FOR WA	NTEE(S	AFT S) Seeks		31		>¢		:	32	90	Ass.	STRA

REPUBLIC OF SOUTH AFRICA PATENTS ACT, 1978

APPLICATION FOR A PATENT AND ACKNOWLEDGEMENT OF RECEIPT BHR (Section 30 (1) - Regulation 22)

REPUBLIEK VAN SUID-AFRIKA

REPUBLIC OF SOUTH AFRICA

The grant of a patent is hereby requested by the undermentioned applicant on the basis of the present application filed in duplicate.

	OFFICIAL APPLICATION NO					
21	01	-2003/2710				
	_					

DMK REFERENCE P26471ZA00

FULL NAME(S) OF APPLICANT(S)

BROSSEUK, Raymond Brian

71

LENER LICENSING

APPLICANTS SUBSTITUTED

ADDRESS(ES) OF APPLICANT(S)

1810 Marley Road Revelstoke British Columbia Canada V03 2S0 Canada STREET POTT POORE SI WAR GOVER

-4. 4. 03

TIT	LE OF INVENTION			
54	STEERING MECHANISM FOR WATERCRAFT			
	THE APPLICANT CLAIMS PRIORITY AS SET OUT ON THE ACCO	OMPANING FOR	M P2	· · · · · · · · · · · · · · · · · · ·
	THIS APPLICATION IS FOR A PATENT OF ADDITION TO PATENT APPLICATION NO.	21	01	
	THIS APPLICATION IS FRESH APPLICATION IN TERMS OF SECTION 37 AND BASED ON APPLICATION NO.	21	01	,

THIS APPLICATION IS ACCOMPANIED BY:

X	1a	A single copy of a provisional specification of 10 pages.
	1b	Two copies of a complete specification of pages.
	2a	Informal drawings of sheets.
×	2b	Formal drawings of 6 sheets.
	3	Publication particulars and abstract (form P8 in duplicate).
	4	A copy of figure of the drawings for the abstract.
	5	Assignment of invention (from the inventors) or other evidence of title.
	6	Certfied priority document(s).
	7	Translation of priority document(s).
	8	Assignment of priority rights.
	9	A copy of form P2 and a specification of S.A. Patent Application. 21 0
	10	A declaration and power of attorney on form P3.
	11	Request for ante-dating on form P4.
	12	Request for classification on form P9.
	13a	Request for delay of acceptance on form P4.

DATED

13b

4 April 2003

ADDRESS FOR SERVICE

74 D M Kisch Inc Inanda Greens Business Park 54 Wierda Road West Wierda Valley SANDTON

The duplicate will be returned to the applicant's address for service as proof of lodging but is not valid unless endorsed with official stamp.

REGISTRAR OF PATENTS DESIGNS,
TRADE MARKS AND COPYRIGHT

OFFICIAL DATE STAMP

REGISTRATEUR VAN PATENTE, MODELLE, HANDELSMERKE EN OUTEURSREG

REPUBLIC OF SOUTH AFRICA

PATENTS ACT, 1978

PROVISIONAL SPECIFICATION

(Section 30 (1) - Regulation 27)

OFFICIAL APPLICATION NO.	LODGING DATE	DMK REFERENCE
21 01 2003/2710	22 4 April 2003	P26471ZA00
FULL NAME(S) OF APPLICANT(S)		·
BROSSEUK, Raymond Brian		-
FULL NAME(S) OF INVENTOR(S)]	
BROSSEUK, Raymond Brian		
TITLE OF INVENTION		
STEERING MECHANISM FOR WATERC	RAFT	
		· · · · · · · · · · · · · · · · · · ·

Title of Invention: STEERING MECHANISM FOR WATERCRAFT

Introduction

5

10

20

This invention relates to a steering mechanism for jet-propelled watercraft.

More particularly, it relates to a steering mechanism for jet-propelled

watercraft that is engaged at varying speeds.

Background of the Invention

Steering devices for watercraft are well-known. The art includes various

references to improved rudders for such craft: US patent 6,428,372, for

example, discloses a pivotally-mounted rudder for a jet-propulsion unit, while

US patent 5,167,547 discloses a pivotally-mounted rudder that is movable

into a steering position.

15 One example of the major disadvantages associated with the current art is

that the watercraft cannot be steered, or cannot be steered satisfactorily if

they are not accelerating, as there is insufficient water passing through the

engine to provide the jet thrust that is required to steer and turn the craft.

When faced with obstacles or other dangerous circumstances in the water,

therefore, an operator of watercraft would necessarily be obliged to

accelerate in order to provide sufficient power to manoeuvre the craft away

from the danger. Such acceleration may often only serve to add to the

2

danger of the situation, particularly for inexperienced operators, and in circumstances in which there is insufficient time to accelerate in order to avoid the danger.

Certain inventions have been directed at the partial alleviation of these disadvantages. In particular, US patent 5,167,547 describes a steering rudder that is selectively operable at the operator's option, while US patent 4,949,662 describes an auxiliary steering means to create a steering effect in a jet propulsion boat at low speeds. Other patents concentrate more generally on the coupling of an actuator on to a rudder (cf: US patent 6,428,372).

While this last-mentioned patent discloses an invention that certainly aids the steering of watercraft, it does little to alleviate the second disadvantage, namely engaging an improved steering mechanism within the critical time available to avoid danger when travelling at low speeds.

Object of the Invention

15

20

It is accordingly an object of the present invention to provide an improved steering mechanism for watercraft that engages automatically at off-throttle conditions, and which, at least partially, overcomes the disadvantages outlined above.

Summary of the Invention

According to the invention there is provided a steering mechanism for jet-

5 propelled watercraft comprising:

a rudder, movable between a steering and a non-steering position, and which

rudder is configured to couple with the steering column of the watercraft

when in the steering position;

securing means for securing the steering mechanism to a watercraft;

10 biasing means for biasing the rudder towards the non-streering position; and

actuating means for actuating the movement of the rudder towards the

steering position automatically, on the speed of the watercraft dropping

below a predetermined level.

15 The securing mechanism is preferably affixed to the outlet nozzle of the

watercraft.

The securing means may incorporate nut-and-bolt fixtures for affixing the

steering mechanism to the body of the watercraft.

20

The rudder may incorporate a plate member located in a substantially ventral

position.

The biasing means may incorporate a spring-loaded engaging member that is configured to engage the plate member of the rudder at high speeds or high nozzle velocities, and to disengage from the plate member at low speeds or low nozzle velocities.

5

10

15

20

In an alternative embodiment of the invention, the biasing means may incorporate a piston-and-lug arrangement that biases the rudder towards the non-steering position, preferably wherein the lugs are coupled to the actuating means.

The actuating means may be coupled to the speedometer, alternatively revolution-counter of the engine, of the watercraft and may incorporate speed-sensitive apparatus which, on the speed, alternatively engine-revolutions, of the watercraft dropping below a predetermined level, overcomes the biasing means to reverse the direction of its bias, allowing the rudder to move towards the steering position.

In an alternative embodiment of the invention, the biasing means may be caused to reverse the direction of its bias via the activation of a source of pressure.

In such an embodiment, the source of pressure may be a pneumatic cylinder.

The source of pressure may be activated by a solenoid.

In a further alternative embodiment of the invention, the actuating means may be coupled to the outflow nozzle of the watercraft, and may incorporate pressure-sensitive apparatus, such as a feedback control device and/or venturi. On the pressure dropping below a predetermined level, the control device compels the biasing means to overcome the bias, allowing the rudder to move towards the steering position.

According to a second aspect of the invention, there is provided a method for the automatic deployment of a steering mechanism in a watercraft, comprising the step of actuating the rudder into the steering position as defined in any of the above consistories.

Brief Description of the Drawings

The invention will now be described in greater detail, by way of example, with reference to the following drawings, in which:

20

15

Figure 1 is a profile view showing a steering mechanism according to a first embodiment of the invention, wherein position I depicts the

rudder in a non-steering position (ie at high speeds), and position II depicts the rudder in a steering position (ie at low speeds);

5 Figure 2

is a perspective view of the steering mechanism according to this embodiment of the invention;

Figure 3a

is a profile view showing the engagement of the rudder and the plate member when in the non-steering position (position I) at high speeds;

10

Figure 3b is a profile view showing the engagement of the rudder and the plate member when in the steering position (position II) at low speeds;

15

Figure 4

is a profile view showing a steering mechanism according to a second embodiment of the invention, wherein position I depicts the rudder in a non-steering position (ie at high speeds), and position II depicts the rudder in a steering position (ie at low speeds);

20

Figure 5 is a pers

is a perspective view of the steering mechanism according to

the second embodiment of the invention; and

Figure 6 is a diagrammatic representation of the actuating means in the second embodiment of the invention.

5

15

20

Detailed Description of the Invention

Referring to the drawings, a steering mechanism in accordance with the invention is provided, referred to generally by numeral 10, incorporates a rudder 20 that is coupled to the steering column (not shown) of the watercraft 30. The steering mechanism 10 is secured to the outlet nozzle 60 of the watercraft 30 by means of a steel nut-and-bolt arrangement 70.

Figures 1, 2 & 3 depict a biasing means according to a preferred embodiment of the invention, wherein the biasing means comprises a plate member 140 and a rudder 20 having a substantially hook-like formation 150 at the terminal end thereof, that is spring-loaded 170. Unlike the plate member 140, which is coupled rigidly to the watercraft 30, the catch member 150 is pivotable about a pivot 160. At low speeds, the terminal end of the rudder 20 drops under gravity and spring tension, and its hook-like formation 150 disengages from the subjacent plate member 140, thereby causing the rudder 20 to move into the steering position as the direction of bias changes.

Conversely, at high speeds, the higher water pressure compels the rudder 20 to pivot in the direction of the water's surface, in which case the hook-like formation 150 engages with the plate member 140.

When, after the speed of the watercraft 30 falls below the predetermined level, the watercraft is caused to accelerate, the increase in water pressure will again cause the rudder 20 to pivot in the direction of the water's surface, and the hook-like formation 150 to engage with the plate member 140 as the rudder becomes biased in the non-steering position. This process of engaging and disengaging the rudder into the steering and non-steering positions respectively may be repeated *ad infinitum*. The rudder 20 is disposed of a further plate member 180, in a substantially ventral position (ie facing the outlet nozzle 60); the further plate member aiding the hydrodynamics of the rudder 20 through water, and thus facilitating the engaging/disengaging process described above.

In an alternative embodiment of the invention, as depicted in Figures 3 & 4, the steering mechanism 10 further incorporates a biasing means comprising pneumatic pistons 40 and lugs 50. The pneumatic pistons 40 are, in turn, coupled to a pneumatic cylinder 80, which forms part of the actuating means (indicated generally by reference numeral 90 in Figure 5).

A further component of the actuating means 90 in this embodiment of the invention is the revolution counter of the engine 100, which is coupled to an electrical solenoid 120 via a switch 110 that is built into the revolution counter 100, and which is activated on the watercraft speed falling below a predetermined level. The solenoid 120, when so activated, permits the opening of a valve 130 on a source of pressure- in this instance, being the pneumatic cylinder 80- which allows for the release of pressure from the pneumatic cylinder 80, causing the displacement of a pneumatic piston 40. This displacement of the pistons 40, in turn, results in a reversal of the direction of the bias of the rudder 20, as it is moved into the steering position.

It will be understood by a person skilled in the art that various embodiments of the invention which are not described herein, are possible, without departing from the spirit and scope of the invention as herein described.


15

10

5

Dated this

Patent Attorney



D.M. KISCH INC.

PATENT ATTERNEYS FOR THE APPLICANT





FIGURE 2


PATENT ATTORNEYS FOR THE APPLICANT

D.M. KISCH INC.

6 SHEETS SHEET 3



6 SHEETS SHEET 4



D.M. KISCH INC.

PATENT ATTORNEYS FOR THE APPLICANT




FIGURE 5

PATENT ATTORNEYS FOR THE APPLICANT

D.M. KISCH INC.




FIGURE 6

PATENT ATTORNEYS FOR THE APPLICANT

D.M. KISCH INC.